



UCAT-40-220

UCAT-40

UCAT-40 Powered Unwinders provide a convenient way to manage your supply roll of labels and also eliminate stress on your printer by feeding labels to the printer. These Powered Unwinders also allow you to use larger supply rolls thereby minimizing your per unit label cost. Additionally, the supply roll doesn't have to be refreshed as often thus saving time and adding convenience.

Technical Specifications	UCAT-40
Max Roll Diameter (in)	16 (406-mm)
Core Diameter (in)	3 (76-mm)
Max Media Width (in) ¹	6 - 10 (152 - 254-mm)
Max Roll Weight (lbs)	20 (9-kg)
Dimensions-HWD (in)	19 x 17 x 17 (482 x 432 x 432-mm)
Weight (lbs) ¹	31 - 33 (14 - 15-kg)
Max Speed (ips)	160 (4064-mm)
Min Speed (ips)	1 (25-mm)
Max Torque (in-oz) ²	228
Max RPM	485
Number of Flanges	1
Power Specifications	120 - 220VAC in, 19VDC 80W Out
Warranty	5 year limited warranty on Unwinder - 1 year limited warranty on Power Adaptor
Available Options	<ul style="list-style-type: none"> • FLANGE, OUT, QC-16 • LTO-CAT (Low-Torque Option) • ADAPT-326 (6" Core Adaptor) • FOOTSWITCH

1. Depends on whether you order the CHUCK, CHUCK-220, or CHUCK-10 model

2. LTO-CAT decreases Torque Range to 172 - 35 in-oz.